


Technical information sheet

Solventum™ Microfluidic Diagnostic

Hydrophilic Film 9938

Effective: August 2022

Supersedes all previous information sheets



Product description

Microfluidic Diagnostic Hydrophilic Film 9938 film consists of a transparent polyester film with one side Solventum hydrophilic treatment and backside treatment designed to stabilize hydrophilic coating when coiled. The product is designed for use in health care medical devices such as test strip and lab-on-chip applications.

Features and benefits

- Hydrophilic
- Transparent
- Non-hemolytic
- Printable
- Non-toxic to mammalian cells
- Dimensionally stable
- Anti-fogging properties

Composition

A. Chemical treatment	Chemical treatment designed to protect and stabilize hydrophilic coating
B. Backing	100 ± 5µm (3.9 ± 0.2 mil) transparent polyester film
C. Hydrophilic coating	Solventum hydrophilic treatment

Please note — The following technical information should be considered representative or typical only and should not be used for specification purposes.

Product properties

Haze	Maximum 4.0%
Light transmission	85~95%
Tensile strength	Minimum – 15 kg/mm ² (2.13 x 10 ⁴ lb/in ²) – machine direction Minimum – 15 kg/mm ² (2.13 x 10 ⁴ lb/in ²) – cross direction
Break elongation, %	Minimum – 80% – machine direction; 80% – cross direction
Heat shrinkage	Maximum – 2.0% – machine direction; 0.5% – cross direction (150°C for 30 minutes)
Wet index value	Minimum – 36

Roll description

Roll length	Maximum 800M (875 yd) ± 2%
Roll width	Minimum 170 ± 3 mm (6.69 ± 0.12 in); Maximum effective (usable) 1040 ± 3 mm (40.94 ± 0.12 in)
Splices per roll	Maximum 1 per every 400M (437 yd); up to 2 per 800M (875 yd)

Note: Supplied on 3-in (76 mm) core for slit roll / 6-in (152 mm) core for 1040mm width log-roll.

Biocompatibility testing: Product 9938 has been subjected to the following safety evaluations


Study type	Test method	Standard	GLP	Result
In vitro cytotoxicity	Cell lysis & cytotoxicity	ISO 10993-5: ≤ 2	Yes	Reactivity grade: 0
MEM elution	Cell lysis & cytotoxicity	ISO 10993-5: ≤ 2	Yes	Reactivity grade: 0
Hemolytic index	Interaction with blood	ISO 10993-4: $< 2\%$	Yes	Non-hemolytic (index: 0.0%)
	Test article extract	ISO 10993-4: $< 2\%$	Yes	Non-hemolytic (index: 0.0%)

Spectroscopy

Integrated emission intensity: Samples were compared to known reference materials, quartz slide, borosilicate slide and quinine sulfate was chosen due to its high purity and stability as a fluorescence standard reference material

Sample	Integrated emission intensity/ 10^6 *
Quartz slide	14.6
Borosilicate cover slide	6.1
3M 9938	503.9
10 ppb quinine in 0.5 N sulfuric acid	82.0

Represents typical value * ($\lambda_{Ex} = 365 \text{ nm}$, $\lambda_{Em} = 450\text{-}650 \text{ nm}$)



Recommended storage & preliminary rollstock shelf life

Product as supplied by Solventum in original packaging will maintain stated properties for a period two (2) years from date stamped on shipping container when stored at temperatures of 50-80°F (10-27°C) and a relative humidity between 40-60 percent.

Please see reverse side for important product, safety and warranty information.

Product and safety information: User is solely responsible for determining the suitability of Solventum samples and products for the intended use including any necessary safety or toxicity assessment. Solventum will provide Material Safety Data Sheets or equivalent and summary results of biocompatibility testing upon request. In every case before using any product in full scale production users should conduct their own tests to determine to their own satisfaction whether the product is of acceptable quality and is suitable for their particular purposes under their own operating conditions.

Notice: Nothing contained herein shall be construed to imply the nonexistence of any relevant patents or to constitute a permission, inducement or recommendations to practice any invention covered by any patent, without authority from the owners of this patent.

Warranty information

All statements, technical information and recommendations herein are based on tests Solventum believes to be reliable, but the accuracy or completeness thereof is not guaranteed. Solventum warrants only that products will meet Solventum's specifications at the time of shipment to the customer. Solventum does not offer any other warranty and does not warrant the performance, safety or such other characteristics of products in combination with other materials. Solventum specifically **does not** warrant products for any intended or unintended uses (whether or not foreseeable); for compatibility or suitability with other components or compatibility with any methods of manufacture or conversion. The foregoing warranty is made in lieu of all other warranties, expressed or implied, including the implied warranties of merchantability, fitness for a particular purpose and freedom from non-infringement.

Limitation of remedies: If products are proven not to meet Solventum's specifications, the sole and exclusive remedy available and Solventum's only obligation shall be, at Solventum's option, to replace such quantity of products which are proven out of specification or to refund the purchase price paid for products.

Limitations of liabilities: The remedies provided herein are exclusive remedies against Solventum for any alleged or actual nonconformance to specifications or defect or other failure in products or for Solventum's performance of its supply obligations. Under no circumstances is Solventum liable for any direct, indirect, incidental, special or consequential damages (including lost profits) in any way related to the product under any theory of law including, but not limited to, negligence and strict liability.

Ordering information

Call us at Customer Service to place an order: 800-742-1994 (U.S.).

Visit our website: go.Solventum.com/MedTechOEM for product and services information, news about conferences we will be attending, new product highlights or to make a direct inquiry.

To have a sales representative contact you, to request samples or clinical and safety summaries, please contact us at Solventum Helpline 800-742-1994 (U.S.) or for international inquiries, please contact your local country representative.



Solventum MedTech OEM

Phone 1-800-742-1994

Web go.Solventum.com/MedTechOEM

©Solventum 2025. Solventum, the S logo and other trademarks are trademarks of Solventum or its affiliates.

791984