

Performance Data Sheet

Model: AP9000, AP9100 and AP9400
Use Replacement Cartridge: **AP9112**

Important Notice: Read this Performance Data Sheet to understand this system's capabilities and confirm whether it meets your water treatment needs. Check your incoming water quality and determine your treatment needs by getting your water tested and/or contacting your local water authority.

System has been tested in accordance with NSF/ANSI Standard 42, 53 and 401 for the reduction of substances listed below. The concentration of the indicated substances in water entering the system was reduced to a concentration less than or equal to the permissible limit for water leaving the system as specified in NSF/ANSI Standard 42, 53 and 401.

Substance	Avg. influent concentration	NSF specified challenge concentration	Avg. % reductions	Avg. product water concentration	Max permissible product water concentration	NSF Reduction Requirements	NSF Test Report
Chlorine Taste & Odor	2.0 mg/L	2.0 mg/L ± 10%	97.6%	> 0.05 mg/L	N/A	50%	A-00433858
Cyst Reduction*	120,000 oocysts/L	≥50,000 oocysts/L	>99.99%	1.0 oocysts/L	N/A	99.95%	J-00273135
Nominal Particulate Class 1, ≥0.5 to < 1.0 micron	5,100,000 particles/mL	≥10,000 particles/mL	99.6%	23,000 particles/mL	N/A	85%	J-00304379
Microplastics	5,100,000 particles/mL	≥10,000 particles/mL	99.6%	23,000 particles/mL	N/A	85%	J-00304379

* Based on the use of *Cryptosporidium parvum* oocysts for testing.

FOR RESIDENTIAL USE ONLY

Application guidelines / water supply parameters	
Capacity	34,069 litres (9,000 gallons)
Service Flow	5.7 lpm (1.5 gpm)
Water Supply	Public or private drinking water supply systems
Water Temperature	4.4° C – 37.8° C (40° F – 100° F)
Water Pressure	172 – 862 kPa (25 -125 psi)

It is essential that the manufacturer's recommended installation, maintenance and filter replacement requirements be carried out for the product to perform as advertised. See Installation Manual for Warranty information.

NOTE: While the testing was performed under standard laboratory conditions, actual performance may vary. Periodically, sanitize the plumbing system with an appropriate disinfectant to maintain the cleanliness of the plumbing lines downstream of the filter.

Flush 11.36 litres (3 gallons) through cartridge(s) before use (flush approximately 2 minutes).

⚠ WARNING
Read entire product manual. Failure to follow all product instructions could cause personal injury from exposure to contaminants and/or property damage due to water leakage or flooding. - DO NOT use with water that is microbiologically unsafe or of unknown quality without adequate disinfection before or after the system. Systems certified for cyst reduction may be used on disinfected water that may contain filterable cysts. - This system does not remove all substances that could be present in drinking water. Test your incoming water quality to identify your treatment needs. After installation, test outgoing filtered water quality regularly to ensure system is installed correctly and meeting your treatment needs, - DO NOT use product if it has been hit, dropped, or damaged. - Before using a new filter cartridge, or whenever system has not been used for more than 72 hours, flush the cartridge with water according to this Performance Data Sheet. - REPLACE FILTER CARTRIDGE no later than every 12 months. If the rated gallon capacity is reached or a noticeable reduction in flow rate, change in odor or taste occurs before 12 months of use, then replace filter promptly. Failure to replace filter cartridge according to these instructions may result in failure of filter to reduce contaminants as designed AND/OR property damage due to water leakage or flooding
NOTICE
Read entire product manual. Failure to follow all product instructions could cause property damage due to water leakage or flooding: - System installation and use must comply with all state and local regulations and plumbing codes. - If your water supply pressure is higher than 80 psi, you must install a pressure reducing valve before installing system. - Protect from freezing. Remove filter cartridge if temperature may drop below 40° F (4.4° C). - REPLACE FILTER CARTRIDGE no later than every 12 months or sooner. Failure to replace the filter cartridge at the required time may lead to property damage due to water leakage or flooding.

Treatment and Tests – Table

System is WaterMark certified to the requirements of drinking water treatment system Standard AS 3497 for the following water treatment category/categories.



Treatment type	Description	Category	Pass
Microbiological status			
Bacteriostatic	Will stop bacteria increasing but will not remove them unless Category II(a) is passed	I	N/A
Microbiological treatment			N/A
Bacteria removal	Will remove or inactivate bacteria	II(a)	N/A
Virus removal	Will remove or inactivate viruses	II(b)	N/A
Protozoa removal	Will remove or inactivate <i>Cryptosporidium</i> and <i>Giardia</i> . Will not remove or inactivate bacteria or viruses unless Category II(a) and Category II(b) are passed	II(c)	✓
Aesthetic effects			
Turbidity and particulate removal	Reduces cloudiness	III	✓
Taste and Odour reduction	Reduces tastes and odours	IV	✓
Chemical treatment			
Chemical contaminant reduction	Will decrease chlorine Will decrease microplastics	V	✓
Other			
Other treatment types not captured in Categories I to V	-	VI	N/A

Legend ✓ = Pass Test N/A = Not Applicable



Solventum Operations Pty Ltd.

Level 3, Building A, 1 Rivett Road,
North Ryde, NSW 2113, Australia
Tel: 1300 FILTER (345 837)

AquaPure.com.au

NSF-PDS-10-986749_2

Solventum and Aqua-Pure are trademarks of Solventum.

WaterMark is a trademark of ABCB.

NSF is a trademark of NSF International.

© Solventum 2025. All rights reserved.